

Christie Automotive

www.christieautomotive.co.uk
info@christieautomotive.co.uk

Timing retard eliminator for Suzuki SV650/S EFI motorcycles FITTING INSTRUCTIONS

Fitting your TRE is quite straightforward. Before starting, please read through these instructions carefully. If you are unsure of your ability to fit the TRE, please ask for help from someone who is technically inclined.

1. Remove both side panels & driver's seat. Prop up the petrol tank



2. The TRE connectors are located next to the tank hinge on LH side.



Unhook the cable clamp.

3. Disconnect the black connector and the natural connector at RH side of hinge.



4. Press the tab to release the black connector.



5. Use a small screwdriver to release the natural connector.




6. The TRE connectors can now be pulled gently out of the frame at the LH side to ease access.



7. Separate the connectors




8. Release the terminals from the male connector by gently lifting the locking tabs with a small screwdriver and pulling the wire from the rear.



9. Fit the new 3-way male connector by gently slipping in the terminals until a click is heard. Cable positions should match TRE male plug.



10. Release the terminals from the female connector by gently lifting the locking tabs with a small screwdriver and pulling the wire from the rear.




11. Fit the new 3-way female connector by gently slipping in the terminals until a click is heard. Cable positions should match TRE female plug.




12. Your TRE can now be plugged into your new connectors. Check that the wire colours match through both sets of connectors. Black to Black, Pink to Pink and Blue to Blue.




13. The TRE can now be held in position by the cable clamp, along with the original wires.



14. Reconnect the black connector and natural connector.



15. Lower the tank and ensure that the TRE and wiring harness are not trapped or fouling.



16. Finally, replace all other components that were previously removed. That's you finished. Enjoy your TRE!

17. To reverse fitment, simply remove TRE and plug new connectors together.

Disclaimer: This product is intended for race use only. Fitting this product may invalidate your manufacturer's warranty. Christie Automotive do not accept liability for any damage/daim in relation to the use of this product. By fitting this product, you acknowledge and signify your agreement with the above statement. A full refund is available to anyone not in agreement with these terms.